

CLAIMS

1. An apparatus for transferring and applying a film of coating solution on each of two applicator rolls to each side of a web as it passes between nipping portions of said two applicator rolls which are formed when they are pressed against each other, said apparatus comprising:
 an air-flotation type mini turn bar, provided to the downstream side of said nipping portions, for conveying said web while holding said web on a surface of one of said two applicator rolls, after said web passes between said nipping portions.
2. The apparatus as set forth in claim 1, further comprising:
 a mechanism for moving said mini turn bar.
3. The apparatus as set forth in claim 2, wherein said mini-turn-bar moving mechanism is constructed to adjust a distance that said web is held on said one applicator roll.
4. The apparatus as set forth in claim 2 or 3, wherein said mini-turn-bar moving mechanism is constructed to adjust a distance between said one applicator roll and said mini turn bar.

5. The apparatus as set forth in any one of claims
1 through 3, further comprising:

5 a paper roll, provided to the upstream side of
said nipping portions, for conveying said web while holding
said web on a surface of the other of said two applicator
rolls, before said web passes between said nipping
portions.

6. The apparatus as set forth in claim 5, further
10 comprising:

 a mechanism for moving said paper roll.

7. An air-flotation type mini turn bar for causing
a web to travel so as to form an arcuately curved portion
15 around said bar by floating said web with air, comprising:

 a first air pocket arranged inside the arcuately
curved portion of said web;

 a second air pocket provided adjacent to said
first air pocket and arranged near an entrance portion
20 of said curved portion;

 a third air pocket provided adjacent to said
first air pocket and arranged near an exit portion of said
curved portion;

 a first air nozzle provided between said first
25 air pocket and said second air pocket for squirting air
toward said web; and

 a second air nozzle provided between said first

air pocket and said third air pocket for squirting air toward said web.

8. The air-flotation type mini turn bar as set forth
5 in claim 7, further comprising:

a third air nozzle for squirting higher-pressure air than atmospheric pressure into said first air pocket.

9. The air-flotation type mini turn bar as set forth
10 in claim 7, further comprising:

a plurality of first baffle walls provided in the direction of the width of said web within said first air pocket so that said first air pocket is segmented into a plurality of sections.

15

10. The air-flotation type mini turn bar as set forth in claim 9, further comprising:

a plurality of second baffle walls provided in the direction of the width of said web within said second
20 air pocket so that said second air pocket is segmented into a plurality of sections; and

a plurality of third baffle walls provided in the direction of the width of said web within said third air pocket so that said third air pocket is segmented into
25 a plurality of sections.

11. The air-flotation type mini turn bar as set forth

in claim 7, wherein:

said second air nozzle comprises a second
air-jet surface and a second slit-shaped air-jet groove,
provided on a third surface extending in the direction
5 of the width of said web;

said second air-jet surface has a great number
of air-jet bores and is provided near said first air pocket;
and

said second air-jet groove extends in the
10 direction of the width of said web and is provided near
said third air pocket.

12. The air-flotation type mini turn bar as set forth
in claim 11, wherein:

15 said first air nozzle comprises a first air-jet
surface and a first slit-shaped air-jet groove, provided
on said third surface extending in the direction of the
width of said web;

said first air-jet surface has a great number
20 of air-jet bores and is provided near said first air pocket;
and

said first air-jet groove extends in the
direction of the width of said web and is provided near
said second air pocket.

25

13. The air-flotation type mini turn bar as set forth
in any one of claims 7 through 12, wherein a shape from

said second air pocket to said third air pocket is formed symmetrically with respect to a center line of said first air pocket.

5 14. An apparatus for transferring and applying a film of coating solution on each of two applicator rolls to each side of a web as it passes between nipping portions of said two applicator rolls which are formed when they are pressed against each other, said apparatus comprising:
10 the air-flotation type mini turn bar as set forth in any one of claims 7 through 13, provided to the downstream side of said nipping portions for conveying said web while holding said web on a surface of one of said two applicator rolls after said web passes between said nipping portions,
15 by air squirted from said bar.

15. A method of transferring and applying a film of coating solution for coated paper production on each of two applicator rolls to each side of a web as it passes
20 between nipping portions of said two applicator rolls which are formed when they are pressed against each other, said method comprising the step of:

 conveying said web while holding said web on a surface of one of said two applicator rolls after said
25 web passes between said nipping portions, by an air-flotation type mini turn bar.